

工业用插头、插座、耦合器（连接器）及接插装置

Industrial Power Plug, Socket, Coupler (Connector)

www.cnmccb.com


工业用插头 Industrial Plug



LK-013-4 LK-023-4

earth contact position	4h	
rated current(A)	16	32
	pole	3
dimension(mm)	a	122 139
	b	59 75
	c	51 64
	Φ	6 8
cable nominal cross-section area(mm ²)	1-2.5	2.5-6


电 流 Current(A): 16A, 32A
电 压 Voltage(V): 110-130V~2P+E
防护等级 Protection degree: IP44



LK-013 LK-023

earth contact position	6h	
rated current(A)	16	32
	pole	3
dimension(mm)	a	122 139
	b	59 75
	c	51 64
	Φ	6 8
cable nominal cross-section area(mm ²)	1-2.5	2.5-6


电 流 Current(A): 16A, 32A
电 压 Voltage(V): 220-240V~2P+E
防护等级 Protection degree: IP44



LK-014 LK-024

earth contact position	6h	
rated current(A)	16	32
	pole	4
dimension(mm)	a	122 139
	b	65 75
	c	55 64
	Φ	6 8
cable nominal cross-section area(mm ²)	1-2.5	2.5-6


电 流 Current(A): 16A, 32A
电 压 Voltage(V): 380-415V~3P+E
防护等级 Protection degree: IP44



LK-015 LK-025

earth contact position	6h	
rated current(A)	16	32
	pole	5
dimension(mm)	a	130 143
	b	72 84
	c	64 70
	Φ	8 8
cable nominal cross-section area(mm ²)	1-2.5	2.5-6


电 流 Current(A): 16A, 32A
电 压 Voltage(V): 220-380V~
240-415V~3P+N+E
防护等级 Protection degree: IP44



LK-033 LK-043

earth contact position	6h	
rated current(A)	63	125
	pole	3
dimension(mm)	a	231.5 293
	b	110 125
	c	16-38 30-50
	Φ	110 125
cable nominal cross-section area(mm ²)	6-16	16-50


电 流 Current(A): 63A, 125A
电 压 Voltage(V): 220-240V~2P+E
防护等级 Protection degree: IP67



LK-034 LK-044


earth contact position	6h	
rated current(A)	63	125
	pole	4
dimension(mm)	a	231.5 293
	b	110 125
	c	16-38 30-50
	Φ	110 125
cable nominal cross-section area(mm ²)	6-16	16-50

电 流 Current(A): 63A, 125A
电 压 Voltage(V): 380-415V~3P+E
防护等级 Protection degree: IP67





电 流 Current(A): 63A, 125A
电 压 Voltage(V): 220-380V~
240-415V~ 3P+N+E
防护等级 Protection degree: IP67




earth contact position		6h	
rated current(A)		63	125
	pole	5	
dimension(mm)	a	231.5	293
	b	110	125
	c	16-38	30-50
	Ø	110	125
	cable nominal cross-section area(mm ²)	6-16	16-50



LK-035 LK-045

电 流 Current(A): 16A, 32A
电 压 Voltage(V): 110-130V~2P+E
防护等级 Protection degree: IP44




earth contact position		4h	
rated current(A)		16	32
	pole	3	
dimension(mm)	a	141	178
	b	59	75
	c	51	64
	Ø	8	10
	cable nominal cross-section area(mm ²)	1-2.5	2.5-6



LK-013L-4 LK-023L-4

电 流 Current(A): 16A, 32A
电 压 Voltage(V): 220-240V~2P+E
防护等级 Protection degree: IP44




earth contact position		6h	
rated current(A)		16	32
	pole	3	
dimension(mm)	a	141	178
	b	59	75
	c	51	64
	Ø	8	10
	cable nominal cross-section area(mm ²)	1-2.5	2.5-6



LK-013L LK-023L

电 流 Current(A): 16A, 32A
电 压 Voltage(V): 380-415V~3P+E
防护等级 Protection degree: IP44




earth contact position		6h	
rated current(A)		16	32
	pole	4	
dimension(mm)	a	141	178
	b	65	75
	c	55	64
	Ø	8	10
	cable nominal cross-section area(mm ²)	1-2.5	2.5-6



LK-014L LK-024L

电 流 Current(A): 16A, 32A
电 压 Voltage(V): 220-380V~
240-415V~ 3P+N+E
防护等级 Protection degree: IP44



earth contact position		6h	
rated current(A)		16	32
	pole	5	
dimension(mm)	a	169	181
	b	72	84
	c	64	70
	Ø	10	10
	cable nominal cross-section area(mm ²)	1-2.5	2.5-6



LK-015L LK-025L