


电 流 Current(A): 16A, 32A
电 压 Voltage(V): 110-130V~2P+E
防护等级 Protection degree: IP44




earth contact position	4h		
rated current(A)	16	32	
	pole	3	
dimension(mm)	a	134	148
	b	80	88
	c	71	71
	d	43.5	57.5
	e	57	57
	f	20	20
	g	32.5	32.5
	h	6.5	6.5
cable nominal cross-section area(mm ²)	1-2.5	2.5-6	

器具插座 Implement Socket



LK-513-4 LK-523-4

电 流 Current(A): 16A, 32A
电 压 Voltage(V): 220-240V~2P+E
防护等级 Protection degree: IP44




earth contact position	6h		
rated current(A)	16	32	
	pole	3	
dimension(mm)	a	134	148
	b	80	88
	c	71	71
	d	43.5	57.5
	e	57	57
	f	20	20
	g	32.5	32.5
	h	6.5	6.5
cable nominal cross-section area(mm ²)	1-2.5	2.5-6	



LK-513 LK-523

电 流 Current(A): 16A, 32A
电 压 Voltage(V): 380-415V~3P+E
防护等级 Protection degree: IP44




earth contact position	6h		
rated current(A)	16	32	
	pole	4	
dimension(mm)	a	139	148.5
	b	80	88
	c	71	71
	d	50	57
	e	57	57
	f	20	20
	g	32.5	32.5
	h	6.5	6.5
cable nominal cross-section area(mm ²)	1-2.5	2.5-6	



LK-514 LK-524

电 流 Current(A): 16A, 32A
电 压 Voltage(V): $\frac{220-380V}{240-415V}$ ~3P+N+E
防护等级 Protection degree: IP44



earth contact position	6h		
rated current(A)	16	32	
	pole	5	
dimension(mm)	a	138.5	150.5
	b	83	90
	c	71	71
	d	55	64
	e	57	57
	f	20	20
	g	32.5	33.5
	h	6.5	6.5
cable nominal cross-section area(mm ²)	1-2.5	2.5-6	



LK-515 LK-525