



3pol 4pol 5pol  
4h 4h 4h

3pol 4pol 5pol  
6h 3h 5h

3pol 4pol 5pol  
9h 6h 6h

3pol 4pol 5pol  
7h 7h 7h

3pol 4pol 5pol  
19h 10h 10h

3pol 4pol 5pol  
2h 2h 2h

3  
2P+E

4  
3P+E

5  
3P+N+E

www.cnmcbb.com


## 第二代器具插座 Second Implement Socket



LK-513-4 LK-523-4

earth contact position	4h	
rated current(A)	16	32
	pole	3
dimension(mm)	a	133
	b	81
cable nominal cross-section area(mm <sup>2</sup> )		1-2.5 2.5-6


电 流 Current(A): 16A. 32A  
电 压 Voltage(V): 110-130V~2P+E  
防护等级 Protection degree: IP44




LK-513 LK-523

earth contact position	6h	
rated current(A)	16	32
	pole	3
dimension(mm)	a	133
	b	81
cable nominal cross-section area(mm <sup>2</sup> )		1-2.5 2.5-6

电 流 Current(A): 16A. 32A  
电 压 Voltage(V): 220-240V~2P+E  
防护等级 Protection degree: IP44



电 流 Current(A): 16A. 32A  
电 压 Voltage(V): 380V-415V~3P+E  
防护等级 Protection degree: IP44




earth contact position	6h	
rated current(A)	16	32
	pole	4
dimension(mm)	a	133
	b	81
cable nominal cross-section area(mm <sup>2</sup> )		1-2.5 2.5-6

LK-514 LK-524



电 流 Current(A): 16A. 32A  
电 压 Voltage(V): 220-380V~3P+N+E  
防护等级 Protection degree: IP44




earth contact position	6h	
rated current(A)	16	32
	pole	5
dimension(mm)	a	133
	b	81
cable nominal cross-section area(mm <sup>2</sup> )		1-2.5 2.5-6

LK-515 LK-525



电 流 Current(A): 63A. 125A  
电 压 Voltage(V): 110-130V~2P+E  
防护等级 Protection degree: IP67




earth contact position	4h		
rated current(A)	63	125	
	pole	3	
dimension(mm)	a	193	
	b	123	
	c	153	
	d	111	
	e	21	
	f	6	
	g	288	
	h	127	
	PG	29	36
	cable nominal cross-section area(mm <sup>2</sup> )		6-16 16-50

LK-5332-4 LK-5432-4



电 流 Current(A): 63A. 125A  
电 压 Voltage(V): 220-240V~2P+E  
防护等级 Protection degree: IP67



earth contact position	6h		
rated current(A)	63	125	
	pole	3	
dimension(mm)	a	193	
	b	123	
	c	153	
	d	111	
	e	21	
	f	6	
	g	288	
	h	127	
	PG	29	36
	cable nominal cross-section area(mm <sup>2</sup> )		6-16 16-50

LK-5332 LK-5432





3pol 4pol 5pol  
4h 4h 4h



3pol 4pol 5pol  
6h 3h 5h



3pol 4pol 5pol  
9h 6h 6h



3pol 4pol 5pol  
7h 7h 7h



3pol 4pol 5pol  
19h 10h 10h



3pol 4pol 5pol  
2h 2h 2h



极数  
3  
2P+E



4  
3P+E




5  
3P+N+E

电 流 Current(A): 63A. 125A

电 压 Voltage(V): 380-415V~3P+E

防护等级 Protection degree: IP67



earth contact position	6h		
rated current(A)	63	125	
	pole 4		
dimension(mm)	a	193	223
	b	123	145
	c	153	185
	d	111	133
	e	21	17
	f	6	8
	g	288	317
	h	127	140
	PG	29	36
cable nominal cross-section area(mm <sup>2</sup> )	6-16	16-50	




LK-5342 LK-5442

电 流 Current(A): 63A. 125A

电 压 Voltage(V): 220-380V~ 240-415V~ 3P+N+E

防护等级 Protection degree: IP67



earth contact position	6h		
rated current(A)	63	125	
	pole 5		
dimension(mm)	a	193	223
	b	123	145
	c	153	185
	d	111	133
	e	21	17
	f	6	8
	g	288	317
	h	127	140
	PG	29	36
cable nominal cross-section area(mm <sup>2</sup> )	6-16	16-50	



LK-5352 LK-5452